


Service Manual

Dolby NR-Equipped
Stereo Cassette Deck

Cassette Deck
RS-B655



Color

(K)... Black Type



Area

Country Code	Area	Color
(E, E5)	Continental Europe.	(K)
(EB)	Great Britain.	
(EG)	F.R. Germany and Italy	

* HX Pro headroom extension originated by Bang Olufsen and manufactured under license from Dolby Laboratories Licensing Corporation. "DOLBY", the double-D symbol, and "HX PRO" are trademarks of Dolby Laboratories Licensing Corporation.

MECHANISM SERIES: AR350

SPECIFICATIONS

CASSETTE DECK SECTION

Deck system	Stereo cassette deck
Track system	4-track, 2-channel
Heads	
Rec/play	Permalloy head
Erasing	Double-gap ferrite head
Motors	
Capstan	Quartz direct drive DC motor
Reel table drive	DC motor
Recording system	AC bias
Bias frequency	80 kHz
Erasing system	AC erase
Tape speed	4.8 cm/sec. (1 7/8 ips)
Frequency response	
NORMAL	20 Hz~18 kHz
	20 Hz~16 kHz (DIN)
CrO ₂	20 Hz~18 kHz
	20 Hz~17 kHz (DIN)
METAL	20 Hz~19 kHz
	20 Hz~18 kHz (DIN)
S/N (signal level=max recording level, CrO ₂ type tape)	
Dolby C NR on	74 dB (CCIR)
Dolby B NR on	66 dB (CCIR)
Dolby NR off	56 dB (A weighted)

Wow and flutter 0.05% (WRMS),
±0.15% (DIN)

Fast forward and rewind times
Approx. 90 seconds with C-60 cassette tape

Input sensitivity and impedance
MIC 0.25 mV/400Ω~10 kΩ
LINE 60 mV/47 kΩ

Output voltage and impedance
LINE 400 mV/800Ω
HEADPHONES 125 mV/8Ω
(8Ω~600Ω)

GENERAL

Power consumption 21W

Power supply

For Great Britain AC 240V, 50/60Hz

For others AC 220V, 50/60Hz

Dimensions (W × H × D)
(16¹⁵/₁₆" × 5¹/₈" × 11¹³/₃₂"

Weight 4.9kg (10.8lb.)

Note:

Specifications are subject to change without notice.
Weight and dimensions are approximate.

Technics

Matsushita Electric Industrial Co., Ltd.

Central P.O. Box 288, Osaka 530-91, Japan

Service Manual


Dolby NR-Equipped
Stereo Cassette Deck

Cassette Deck
RS-B655



Color

(K)...Black Type



Area

Country Code	Area	Color
(E, E5)	Continental Europe.	(K)
(EB)	Great Britain.	
(EG)	F.R. Germany and Italy	

* HX Pro headroom extension originated by Bang Olufsen and manufactured under license from Dolby Laboratories Licensing Corporation. "DOLBY", the double-D symbol, and "HX PRO" are trademarks of Dolby Laboratories Licensing Corporation.

MECHANISM SERIES: AR350

SPECIFICATIONS

CASSETTE DECK SECTION

Deck system	Stereo cassette deck
Track system	4-track, 2-channel
Heads	
Rec/play	Permalloy head
Erasing	Double-gap ferrite head
Motors	
Capstan	Quartz direct drive DC motor
Reel table drive	DC motor
Recording system	AC bias
Bias frequency	80 kHz
Erasing system	AC erase
Tape speed	4.8 cm/sec. (1 7/8 ips)
Frequency response	
NORMAL	20 Hz~18 kHz
CrO ₂	20 Hz~16 kHz (DIN)
METAL	20 Hz~18 kHz
METAL	20 Hz~17 kHz (DIN)
METAL	20 Hz~19 kHz
METAL	20 Hz~18 kHz (DIN)
S/N (signal level=max recording level, CrO ₂ type tape)	
Dolby C NR on	74 dB (CCIR)
Dolby B NR on	66 dB (CCIR)
Dolby NR off	56 dB (A weighted)

Wow and flutter 0.05% (WRMS)
±0.15% (DIN)

Fast forward and rewind times

Approx. 90 seconds with C-60 cassette tape

Input sensitivity and impedance

MIC	0.25 mV/400Ω~10 kΩ
LINE	60 mV/47 kΩ

Output voltage and impedance

LINE	400 mV/800Ω
HEADPHONES	125 mV/8Ω (8Ω~600Ω)

GENERAL

Power consumption 21 W

Power supply

For Great Britain	AC 240V, 50/60 Hz
For others	AC 220V, 50/60 Hz

Dimensions (W × H × D)

430 × 135 × 290 mm
(16¹⁵/₁₆" × 5¹/₈" × 11¹³/₃₂")

Weight

4.9 kg (10.8 lb.)

Note:

Specifications are subject to change without notice.
Weight and dimensions are approximate.


Technics

Matsushita Electric Industrial Co., Ltd.
Central P.O. Box 288, Osaka 530-91, Japan

CONTENTS

	Page		Page
CONNECTIONS.....	2	TROUBLESHOOTING OF DIRECT DRIVE MOTOR.....	26
ACCESSORIES	2	TERMINAL GUIDE OF IC'S,	
FRONT PANEL CONTROLS AND FUNCTIONS.....	3, 4	TRANSISTORS AND DIODES	27
RECORDING WITH HIGH TONE QUALITY.....	5	PRINTED CIRCUIT BOARDS.....	28~32
OUTLINE OF THE DIRECT DRIVE MOTOR SYSTEM.....	6	WIRING CONNECTION DIAGRAM	33
DISASSEMBLY INSTRUCTIONS.....	7~10	REPLACEMENT PARTS LIST.....	34~36
MEASUREMENT AND ADJUSTMENT METHODES....	11~13	EXPLODED VIEWS.....	37~40
TERMINAL FUNCTION OF IC'S.....	14, 15	REPLACEMENT PARTS LIST	41
BLOCK DIAGRAM.....	16, 17	RESISTORS & CAPACITORS	42~44
INTERNAL CONNECTION OF FL.....	18	PACKING.....	44
SCHEMATIC DIAGRAM	19~26	※ TECHNICAL INFORMATION	
		※ This technical information is located on pp 45-51 of the	
		RS-B555 Service Manual (Order No. AD8907231C5).	
		Therefore, refer to that Service Manual.	


CONNECTIONS



ACCESSORIES

- Stereo connection cables 2
[SJP2249-3]
- AC power supply cord 1
[SFDAC05E03: (E, E5, EG)]
[SJA193-1: (EB)]

FRONT PANEL CONTROLS AND FUNCTIONS



1 Power “standby ⏻/on” switch (power “standby ⏻/on”)

This switch switches ON and OFF the secondary circuit power only. The unit is in the “standby” condition when this switch is set to the “standby ⏻” position. Regardless of the switch setting, the primary circuit is always “live” as long as the power cord is connected to an electrical outlet.

2 Eject button (▲eject)

This button can be used to open the cassette holder.

3 Cassette holder

4 Display section

5 Recording-level control (rec level)

This control can be used to regulate the recording level and the peak level.

6 Recording-balance control (balance)

Use this control to balance the left and right sound levels during recording.

7 Microphone jacks (mic)

8 Bias-adjustment control (bias adjust)


The frequency response for each tape type can be equalized by using this control.

9 Operation section

10 Headphones jack (phones)

11 Headphones volume control (phones level)

Display section



A Input level meter (peak level)

During playback, this meter indicates the level of the recorded sound.

During recording, it indicates the level being recorded, adjusted by the recording-level control.

B Tape/Linear counter

Indicates the amount of tape movement or elapsed time.

C Memory-mode indicators (memory stop/repeat)

Each indicator illuminates to show which of the memory mode was set by the memory-mode buttons.

D Tape-select indicators

The type of tape being used will be automatically detected and the indicator will illuminate.

E APRS indicator (APRS)

Illuminates to indicate that the "APRS" is set to "on" in the recording stand-by mode.


F Multiplex filter indicator (MPX)

Illuminates to indicate that the multiplex filter is set to "on".

G Dolby noise-reduction indicators (B, C)

Each indicator illuminates to show the type of Dolby noise-reduction system selected by pressing one of the Dolby noise-reduction buttons.

Operation section

**1 Timer switch (timer)**

This switch is used to automatically begin a tape recording or tape playback at a certain time, selected by a timer (not included).

2 Counter buttons (counter reset/mode)

mode: This button can be used to select the tape/linear counter indication.

reset: This button can be used to reset the tape/linear counter indication to "0000".

3 Memory-mode buttons (memory repeat/stop)

stop: This button can be used to rewind the tape to the preset "0000" point when the rewind (◀◀) button is pressed.

repeat: This button can be used to set this unit to the "A-B repeat" mode.

4 Meter-range selector (meter range)

This selector can be used to select the meter-range display of the input level meter.

5 Multiplex filter switch (MPX filter)

This switch can be used during the recording of an FM stereo broadcast that employs Dolby noise reduction so as to prevent misoperation of the Dolby noise reduction.

6 Dolby noise-reduction buttons (noise reduction)

These buttons are used to reduce the hissing noise heard from the tape. This unit is provided with both the B-type and C-type noise-reduction systems.

7 APRS button (APRS)

This button can be used to hold the peak level while monitoring the input sound.
The "APRS" can only be used in the recording stand-by mode.

8 Record button and indicator (rec/●)

This button can be used to change the tape deck to the recording stand-by mode.

This indicator illuminates to indicate that this tape deck is in the recording stand-by mode, or is recording.

9 Automatic-record-muting button (auto rec mute/○)

This button can be used to make a silent interval on the tape being recorded on tape deck.

10 Pause button (pause/II)

This button can be used to temporarily stop the tape playback or recording of tape deck.

11 Rewind/fast-forward/search buttons (rew/◀◀/ff/▶▶)

These buttons can be used to fast forward or rewind the tape, or to easily search for the tune's beginning of the tape quickly.

12 Playback button and indicator (play/▶)

This button can be used to start the playback or recording of the cassette.


(The tape will then begin moving in the left-to-right direction.)

When this indicator illuminates steadily, it indicates that this tape deck is in the playback mode or the recording mode. When it flashes continually, this is an indication that this tape deck is in the pause mode or the recording stand-by mode.

13 Stop button (stop/■)

This button can be used to stop tape movement.

RECORDING WITH HIGH TONE QUALITY



APRS function

Because the dynamic range of cassette tape is narrower than the dynamic range of a digital source, the recording will be too noisy if the recording level setting is too low, and, conversely, the recorded sound will be distorted if the setting is too high.

It was for this reason that it has always been recommended that the signals to be recorded be first (before recording) input to the cassette deck and the recording level then be set while watching the level meter, but, for former conventional level meter equipped with the peak-hold function, it was necessary to re-adjust and input the signals again if the level setting was too high or too low.

This unit, however, is equipped with the **APRS: Advanced Precise Recording-level System**, which holds and displays the maximum peak of the input signal level, so that once the peak level of the source is held, there is no necessity to re-input the source signals, and the optimum recording level can be set.

•The APRS function can be used only during the recording-standby mode.

1 Prepare for recording as described in steps 1 to 6 of the "Recording" section.

2 rec

Press the record button.

(The recording indicator will illuminate and the playback indicator will flash continuously; the unit will be in the recording stand-by mode.)

3 rec level / balance

Set the recording-level control and the recording-balance control to the suitable position for the sound source.

4 APRS

Press the APRS button.

(The APRS indicator will illuminate.)

5 Play the sound source to be recorded, from beginning to end.

[The peak level (the highest level of the input signal) of the sound source will be displayed and held on the input-level meter.]

Input level meter



Peak level

Note:

The range within which the peak level can be held is -8 dB to $+16$ dB. Note that the APRS indicator will flash continuously if the peak level of the sound source is input at a level that exceeds the maximum recording level ($+16$ dB).

If that happens, press the APRS button to cancel the APRS function, and then reset the recording level and set the APRS once again.

Also note that the peak level cannot be held to less than -8 dB.

6 rec level

Using the recording-level control, adjust the peak level to the desired setting.

The peak level will move to the right when the recording-level control is turned to the right, and will move to the left when the recording-level control is turned to the left.

•The recording-balance control cannot be used to adjust the peak level.

7 Begin playing the sound source from the beginning once again.

8 play


Press the playback button.

(The playback indicator will illuminate steadily, and the recording will begin.)

The APRS indicator will switch OFF, and the indication of the input-level meter will return to the ordinary peak-hold mode.

■ OUTLINE OF THE DIRECT DRIVE MOTOR SYSTEM







The capstan motor is actuated by the DD motor digital servo system. The FG pulse is generated after the detection of the zero crosspoint, and the reference signal generated from the quartz oscillator is compared with this FG pulse. From this comparison, the accelerated and reduced speed pulses are generated, causing the driving coil to function.



DISASSEMBLY INSTRUCTIONS

"ATTENTION SERVICER"


Some chassis components may have sharp edges. Be careful when disassembling and servicing.

Ref. No. 1	Removal of the cabinet	Ref. No. 2	Removal of the main P.C.B.
Procedure 1	 <p>• Remove the 6 screws (①~⑥).</p>	Procedure 1→2	<p>1. Remove the 7 screws (①~⑦). 2. Remove the rear panel from the projection of the bottom chassis.</p>
	<p>3. Remove the 6 screws (⑧~⑬). 4. Remove the 1 connector (CP2). 5. Remove the 4 flat cables (CN3, CN4, CN6, CN201). 6. Remove the main P.C.B. in the direction of the arrow.</p> <p>How to remove the flat cable</p> <p>• Pull out the flat cable while pressing the connector.</p> <ol style="list-style-type: none"> 1. Lift the connector. 2. Pull out the flat cable. 		 
	<p>How to check the main P.C.B.</p> <p>• When checking the soldered surfaces of main P.C.B. and replacing the parts, do as show.</p> <ol style="list-style-type: none"> 1. Remove the 9 screws (①, ③, ⑦~⑬) in above figure. 2. Remove the 4 screws (⑭~⑰). 3. Remove the front panel in the direction of the arrow A. 		<ol style="list-style-type: none"> 4. Remove the bottom board in the direction of the arrow B. 5. Reinstall the front panel to the main P.C.B. 

Ref. No.
3


Removal of the front panel

Procedure
1→3



1. Remove the 4 screws (1~4).

2. Remove the 1 connector (CP2).
3. Remove the 4 flat cables (CN3, CN4, CN6, CN201).




4. Remove the front panel in the direction of the arrow.


Ref. No.
4

Removal of the power switch/ headphones P.C.B.

Procedure
1→3→4



1. Remove the power switch button by pushing it from behind the front panel.
2. Pull out the headphones level knob.




3. Remove the 2 screws (1, 2).
4. Release the 1 claw.


Ref. No.
5

Removal of the mechanism unit






Procedure
1→3→5





1. Push the eject button.



2. Remove the 4 screws (1~4).

Ref. No. 6 Procedure 1→3→6	Removal of the FL drive P.C.B.	 <p>FL Drive P.C.B.</p> <p>Claw</p> <ol style="list-style-type: none"> 2. Remove the 6 screws (①~⑥). 3. Release the 2 claws. 4. Remove the FL drive P.C.B. in the direction of the arrow.
Ref. No. 7 Procedure 1→3→6→7	Removal of the mic jack P.C.B.	Ref. No. 8 Procedure 1→3→6→8
 <p>Mic Jack P.C.B.</p> <p>• Remove the mic jack P.C.B. in the direction of the arrow.</p>		 <p>Rec Level Knob</p> <p>Nut</p> <p>Rec Level P.C.B.</p> <ol style="list-style-type: none"> 1. Pull out the rec level knob. 2. Remove the 1 nut.
Ref. No. 9 Procedure 1→3→6→9	Removal of the operation P.C.B.	Ref. No. 10 Procedure 1→3→5→10
 <p>Claws</p> <p>Operation P.C.B.</p> <p>Claw</p> <ol style="list-style-type: none"> 1. Remove the 4 screws (①~④). 2. Release the 4 claws. 		 <p>Damper Gear</p> <p>• Remove the 1 screw (①).</p>

Ref. No. 11	Removal of the cassette holder	<ol style="list-style-type: none"> 1. Remove the rib in the direction of the arrow. 2. Remove the cassette holder spring. 3. Pull out the cassette holder in the direction of the arrow.
Procedure 10→11		
Ref. No. 12	Removal of the eject lever and eject button	
Procedure 1→3→4→5→12	<ol style="list-style-type: none"> 1. Push the claw in the direction of the arrow A. 2. Remove the eject lever in the direction of the arrow B. 	

MEASUREMENT AND ADJUSTMENT METHODES

Measurement Condition

- Rec. level control; Maximum
- Timer switch; Off
- MPX filter switch: off
- Bias-adjustment VR: Center

- Dolby NR switch; Off
- Make sure heads are clean
- Make sure capstan and pressure roller are clean
- Judgeable room temperature $20 \pm 5^{\circ}\text{C}$ ($68 \pm 9^{\circ}\text{F}$)

Measuring Instrument

- EVM (Electronic Voltmeter)
- Oscilloscope
- Digital frequency counter
- AF oscillator


- ATT (Attenuator)
- DC voltmeter
- Resistor (600Ω)

Test tape

- Head azimuth adjustment (8kHz, -20dB); QZZCFM
- Tape speed adjustment (3kHz, -10dB); QZZCWAT
- Playback frequency response (315Hz, 12.5kHz, 10kHz, 8kHz, 4kHz, 1kHz, 250Hz, 125Hz, 63Hz, -20dB); QZZCFM

- Playback gain adjustment (315Hz, 0dB); QZZCFM
- Overall frequency response, Overall gain adjustment
Normal reference blank tape; QZZCRA
CrO₂ reference blank tape; QZZCRX
Metal reference blank tape; QZZCRZ

Adjustment Points



HEAD AZIMUTH ADJUSTMENT

1. Playback the azimuth adjustment portion (8 kHz, -20 dB) of the test tape (QZZCFM). Vary the azimuth adjusting screw until the outputs of the L-CH and R-CH are maximized and the lissajous waveform, as illustrated, approaches 0 degrees.

Note: If L-CH and R-CH are not maximized at the same point, adjust to the point where the levels of each channel are maximized and equal.

2. Perform the same adjustment in the play mode.

3. After the adjustment, apply screwlock to the azimuth adjusting screw.





Fig. 1

Record/Playback Head



Azimuth Screw

Fig. 2

PLAYBACK GAIN ADJUSTMENT

1. Playback the gain adjusted portion (315 Hz, 0 dB) of the test tape (QZZCFM).

2. Adjust VR1 (L-CH) and VR2 (R-CH) so that the output is within the standard value.

Standard value: $0.4V \pm 0.5dB$




Fig. 3

PLAYBACK FREQUENCY RESPONSE

1. Playback the frequency response portion (315 Hz, 12.5 kHz ~ 63 Hz, -20 dB) of the test tape (QZZCFM).
2. Assume that the frequency response is within the range shown in Fig. 6 for both L-CH and R-CH.




Fig. 4





Fig. 5

AC BIAS TRAP ADJUSTMENT

1. Insert the Metal blank test tape (QZZCRZ) and set the unit to the Record mode.
2. Adjust L1 (L-CH) [[L2 (R-CH)]] so that the output voltage between TP1 (TP2) and GND is less than the minimum value.



OVERALL FREQUENCY RESPONSE

1. Insert the normal blank test tape (QZZCRA) and set the unit to the record pause mode.
2. Apply a reference input signal (1 kHz, -24 dB) through an attenuator.
3. Attenuate the signal by 20 dB and adjust the frequency from 50 Hz ~ 10 kHz.
4. Record the frequency sweep.
5. Playback the recorded signal and assure that it is within the range shown in Fig. 8 in comparison to the reference frequency (1 kHz).
6. If it is not within the standard range, adjust **VR301** (L-CH) and **VR302** (R-CH) so that the frequency level is within the standard range.
 - Level up in high frequency rangeIncrease the bias current.
 - Level down in high frequency range ...Decrease the bias current.
7. Repeat steps 2~6 above using the CrO₂ tape (QZZCRX) and the metal tape (QZZCRZ) increasing the frequency range to 12.5 kHz (50 Hz ~ 12.5 kHz).
8. Assure that the level is within the range shown in Fig. 9.




Fig. 10

Normal Overall frequency response chart (NR OUT)




Fig. 8

CrO₂ Metal Overall frequency response chart (NR OUT)




Fig. 9

OVERALL GAIN ADJUSTMENT

1. Insert the normal blank test tape (QZZCRA) and set the unit to the record pause mode.
2. Apply a reference input signal (1 kHz, -24 dB). Attenuate the output so that its level becomes 0.4 V.
3. Record this input signal.
4. Playback the signal recorded in step 3 above, and assure that the output is within the standard value.
5. If it is not within the standard value, adjust **VR3** (L-CH) and **VR4** (R-CH).
6. Repeat the step 2~5 above until the output is within the standard value.

Standard value: $0.4V \pm 0.5dB$




Fig. 11

■ TERMINAL FUNCTION OF IC'S

• IC901 (MB88511-224N): MICROCOMPUTER (This microcomputer is used for mechanical operation.)


Pin No.	Mark	I/O Division	Function
1	DMT	O	Line out mute signal ("H"...ON, "L"...OFF)
2	RMT	O	REC AMP mute signal ("H"...ON, "L"...OFF)
3	$\overline{\text{BOS}}$	O	BIAS OSC ON/OFF control signal ("H"...OFF, "L"...ON)
4	$\overline{\text{REC}}$	O	REC LED ON/OFF control signal ("H"...OFF, "L"...ON)
5	$\overline{\text{PLAY}}$	O	PLAY LED ON/OFF control signal ("H"...OFF, "L"...ON)
6	EJECT F	O	Power eject motor open control signal ("H"...OPEN, "L"...CLOSE/STOP)
7	EJECT R	O	Power eject motor close control signal ("H"...CLOSE, "L"...OPEN/STOP)
8	$\overline{\text{CAPM}}$	O	Capstan motor ON/OFF control signal ("H"...OFF (POWER OFF or ABNORMAL CONDITION), "L"...ON)
9	$\overline{\text{SOL1}}$	O	Trigger solenoid ON/OFF control signal ("H"...OFF, "L"...ON)
10	$\overline{\text{SOL2}}$	O	Brake solenoid ON/OFF control signal ("H"...OFF, "L"...ON)
11	$\overline{\text{SOL2C}}$	O	Brake solenoid hold ON/OFF control signal ("H"...OFF, "L"...ON (FF/REW/MS))
12	RP (REEL PULSE)	I	Reel pulse signal
13	RMR	O	Reel motor reverse control signal ("H"...REW, "L"...STOP/PLAY/FF)
14	RMF	O	Reel motor forward control signal ("H"...FF/PLAY, "L"...STOP/REW)
15	$\overline{\text{OSC}}$	I	Single capstan/Dual capstan select signal ("H"...DUAL CAPSTAN, "L"...SINGLE CAPSTAN)
		O	Calibration OSC circuit ON/OFF control signal ("H"...OFF, "L"...ON)
16	Ex	I	Clock OSC terminal (6MHz)
17	X	O	
18	$\overline{\text{RES}}$	I	Reset signal ("L"...RESET)
19	OSCF	O	Calibration OSC circuit (400Hz/10kHz) select signal ("H"...HIGH FREQ. (10kHz), "L"...LOW FREQ. (400Hz))
20	$\overline{\text{POF}}$	I	AC POWER detect signal
21	Vss	—	GND

Pin No.	Mark	I/O Division	Function					
22	$\overline{\text{DIRECT}}$	I	CD direct operation det. signal					
		O	CD direct/LINE input select control signal ("H"...CD DIRECT, "L"...LINE INPUT)					
23	$\overline{\text{C}}$	O	Dolby NR mode select signal		NR OFF	Dolby B	Dolby C	dbx
24	$\overline{\text{B}}$			$\overline{\text{C}}$ $\overline{\text{B}}$	H H	H L	L H	L L
25	MPX	O	MPX coil ON/OFF control signal ("H"...MPX OFF, "L"...MPX ON)					
26	$\text{T}/\overline{\text{S}}$	I	Two head/Three head select signal ("H"...THREE HEAD, "L"...TWO HEAD)					
		O	Tape/Source monitor select control ("H"...TAPE MONITOR, "L"...SOURCE MONITOR)					
27	$\overline{\text{HALF}}$	I	Cassette half det. SW terminal ("L"...ON)					
28	$\overline{\text{MODE}}$	I	Mechanism mode SW terminal					
29	$\overline{\text{ARM}}$	I	Auto Rec Mute key signal ("L"...PUSH)					
30	AVss	—	Connected to GND					
31	$\text{AV}\overline{\text{R}}$	—	Connected to GND					
32	AVcc	—	Power supply terminal					
33	KEY 1	I	Key SW input (STOP/FF REW/PLAY/REC/PAUSE/dbx/C/B/MPX/TIMER REC/TIMER PLAY)					
34	KEY 2	I	Key SW input (MEMORY REPEAT/MEMORY STOP/EJECT/MONITOR/CD DIRECT/OSC/TEST/REMOTE A/B)					
35	ATS	I	Auto Tape Select SW input (ATSC/ATSM/EJECT OPEN LEAF SW)					
36	INH	I	REC INH SW input (REC INH/EJECT MOTOR LEAF SW)					
37	B555	I	Connected to GND					
38	DISP	O	Serial data signal of FL display (ACTIVE: "H")					
39	MSP	I	Music select det. signal ("H"...NO SIGNAL, "L"...ON SIGNAL)					
40	$\overline{\text{MEMORY PULSE}}$	I	Memory Pulse signal					
41	$\overline{\text{REMOCON}}$	I	Remote control serial data ("L" for 50ms. with counter "0000")					
42	Vcc	—	Power supply terminal					

■ BLOCK DIAGRAM


Pin No.	Mark	I/O Division	Function
1	S5	O	Segment signal for FL display
2	S6	O	
3	S7	O	
4	Vdisp	—	Pull down power supply terminal (–Vcc)
5	S8	O	Segment signal for FL display
6	S9	O	
7	S10	O	
8	S11	O	
9	S12	O	
10	S13	O	
11	S14	O	
12	S15	O	
13	S16	O	
14	S17	O	
15	S18	O	
16	S19	O	
17	RPT	I	Reel pulse signal of tape up reel
18	RPS	I	Reel pulse signal of supply reel
19	MP	O	Memory pulse signal ("L" for 50 ms. with counter "0000")
20	DISP	I	Serial data signal (ACTIVE: "H")
21	GND	—	GND terminal

Pin No.	Mark	I/O Division	Function
22	AVcc	—	Power supply terminal
23	VR IN	I	Rec level control (VR MAX... +5V)
24	F IN	I	Function key terminal (COUNTER RESET/COUNTER MODE/APRS)
25	SIG L	I	LCH level signal
26	SIG R	I	RCH level signal
27	AVss	—	Connected to GND
28	RESET	I	Reset terminal (with Reset: "H")
29	$\overline{\text{TEST}}$	I	Test terminal
30	OSC 1	O	Clock OSC terminal (4MHz)
31	OSC 2	I	
32	Vcc	I	Power supply terminal
33	G1	O	Grid signal for FL display
34	G2	O	
35	G3	O	
36	G4	O	
37	G5	O	
38	G6	O	
39	S1	O	Segment signal for FL display
40	S2	O	
41	S3	O	
42	S4	O	















































INTERNAL CONNECTION OF FL

- **Grid connection diagram**




- **Anode connection table**

	1G	2G	3G	4G	5G	6G
S1	S1	LEVEL CAL	-	APRS	-	-
S2	S2	BIAS CAL	-	-	-	-
S3			-	-	-	-
S4			-	-	-	-
S5			-	-	-	-
S6			-	-	memory	-
S7			-	-	repeat	-
S8			-	-	stop	-
S9				-	-	-
S10				-	I /Normal	-
S11			-	MPX	II /CrO ₂	-
S12					IV/Metal	-
S13			a	a	a	a
S14			b	b	b	b
S15			f	f	f	f
S16			g	g	g	g
S17			c	c	c	c
S18			e	e	e	e
S19			d	d	d	d
S20 (dB)	left  dB right 				-	

- **Pin connection**

PIN NO.	40	39	38	37	36	35	34	33	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
CONNECTION	N	N	N	N	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	N	G	6	5	4	3	2	1	S	N	N	N	N	N	N	N	F	F
	P	P	P	P	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	C	G	G	G	G	G	20	P	P	P	P	P	P	P	1	1	

[illegible]

Notes

-  Playback signal
-  Recording signal

SCHEMATIC DIAGRAM

(Parts list on pages 34, 35, 42~44.)

(This schematic diagram may be modified at any time with development of new technology.)

Notes:

- S701 : Stop switch (stop) in "off" position.
- S702 : F.F. switch (ff) in "off" position.
- S703 : Rew switch (rew) in "off" position.
- S704 : Playback switch (Play) in "off" position.
- S705 : Record switch (rec) in "off" position.
- S706 : Pause switch (pause) in "off" position.
- S707 : Dolby noise-reduction switch (Dolby NRC) in "off" position.
- S708 : Dolby noise-reduction switch (Dolby NR B) in "off" position.
- S709 : Multiplex filter switch (MPX filter) in "off" position.
- S710 : Timer switch (timer) in "off" position.
- S711 : Counter reset switch (counter reset) in "off" position.
- S712 : Counter mode switch (counter mode) in "off" position.
- S713 : Meter range switch (meter range) in "off" position.
- S714 : Memory mode switch (memory repeat) in "off" position.
- S715 : Memory mode switch (memory stop) in "off" position.
- S716 : APRS switch (APRS) in "off" position.
- S717 : Automatic-record-muting switch (auto rec mute) in "off" position.
- S718 : Power switch (standby ϕ /on) in "on" position.
- S971 : Mode switch in "off" position.
- S972 : Cassette half detection switch in "off" position.
- S973 : ATS (CrO₂) switch in "off" position.
- S975 : Rec Inhibit switch in "off" position.
- S976 : ATS (Metal) switch in "off" position.

• Resistance are in ohms (Ω), 1/4 watt unless specified otherwise.

1K=1,000 (Ω), 1M=1,000k (Ω)

• Capacity are in micro-farads (μ F) unless specified otherwise.

• All voltage values shown in circuitry are under no signal condition and playback mode with volume control at minimum position otherwise specified.

()Voltage values at record mode.

For measurement us EVM.

Important safety notice

Components identified by Δ mark have special characteristics important for safety. When replacing any of these components, use only manufacturer's specified parts.

• ($\text{---} < +B > \text{---}$) indicates +B (bias).

• ($\text{---} < -B > \text{---}$) indicates -B (bias).

• ($\text{---} < \text{PLAYBACK} > \text{---}$) indicates the flow of the playback signal.

• ($\text{---} < \text{RECORD} > \text{---}$) indicates the flow of the record signal.

* Caution!

IC and LSI are sensitive to static electricity.


Secondary trouble can be prevented by taking care during repair.


* Cover the parts boxes made of plastics with aluminum foil.


* Ground the soldering iron.

* Put a conductive mat on the work table.

* Do not touch the legs of IC or LSI with the fingers directly.








※ These are the parts for MPX effect adjustment.
When these parts are supplied, they have been adjusted.
Thus it does not need to readjust when you change these parts.

F REC LEVEL VR CIRCUIT

B FL METER CIRCUIT

G POWER SWITCH/HEADPHONES JACK CIRCUIT

H OPERATION




■ TROUBLESHOOT

Problem	
1. The motor does not rotate.	1. N 2. T n 3. T
2. The motor does not rotate properly. (When pressed, it stops at certain angles. Sometimes it does not rotate even if power is ON.)	1. T 2. O
3. The motor is out of control.	1. T
4. Abnormal wow	1. S


Note: Check the points marked with pin ② to GND with a lead wire (the coil, heating the IC.)

TERMINAL GUIDE OF IC'S, TRANSISTORS AND DIODES

I CAPSTAN MOTOR(D.D) CIRCUIT



J FG CIRCUIT



TROUBLESHOOTING OF DIRECT DRIVE MOTOR

Problem	Possible Cause	Check Points
1. The motor does not rotate.	1. No power supply (+12V) 2. The Hall element has failed (Current does not flow). 3. The ceramic (or crystal) does not oscillate.	• Check the voltage applied to the connector. • Check the DC potential on IC pins ②~⑦. *Check the waveform of IC pin ⑬.
2. The motor does not rotate properly. (When pressed, it stops at certain angles. Sometimes it does not rotate even if power is ON.)	1. The coil is broken or not properly soldered. 2. Output of the Hall element is not proper.	*Check the conductance of the coil. If normal, the resistances between IC pins ⑬~⑭, ⑭~⑮, ⑮~⑯ will reach 20 ohms. • Check the waveform of IC pins ②~⑦.
3. The motor is out of control.	1. The FG coil is broken.	• Check the waveform of IC pin ⑤. • Check if the FG coil is broken.
4. Abnormal wow	1. Same as those described for problem 2.	


Note: Check the points marked with an asterisk (*) by removing the DD motor control P.C.B. and then connecting IC pin ② to GND with a lead wire. (After the DD motor control P.C.B. is removed, current will start flowing through the coil, heating the IC.)


	UPC1297CA 18 Pin TEA0665 28 Pin AN7351K 42 Pin HD404302SA07 42 Pin MB88511-224N 42 Pin		HA13440MPEL 30 Pin
	M5218L 8 Pin BA6218 9 Pin		2SJ164PQRTA
	2SB621ARSTA 2SD592A		2SA1309AQSTA 2SC3311AQSTA 2SD1450RSTTA 2SB1030RSTTA
	DTC114ESTP DTC114YSTP		DTA114ESTP
	2SB1357DEFTA 2SD2037EFTA		MA167TA MA165TA 1SR35200TB 1SS133
	MA4200M MA4047MTA MA4091MTA MA4062HTA MA4120M MA4330MTA MA4056H MA4051MTA MA4056MTA		2SK381BCDTA
	2SD601RTW		SN74LS04MEL 14 Pin SN74LS74AMEL 14 Pin
	MA3056MTW		MA3056MTW

PRINTED CIRCUIT BOARDS


A
B
C
D
E
F
G

1 2 3 4 5 6 7 8 9 10




B FL METER P.C.B.


H OPERATION SWITCH P.C.B.




G POWER SWITCH/HEADPHONES JACK P.C.B.




E REEL MOTOR P.C.B.




A MIC JACK P.C.B.



F REC LEVEL VR P.C.B.



[illegible]

REPLACEMENT PARTS LIST

Notes : * Important safety notice:

Components identified by Δ mark have special characteristics important for safety. When replacing any of these components use only manufacturer's specified parts.

- * The parenthesized indications in the Remarks columns specify the areas. (Refer to the cover page for area.)

Parts without these indications can be used for all areas.

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		INTEGRATED CIRCUIT(S)		Q905	DTA114ESTP	TRANSISTOR	
				Q906	DTC114ESTP	TRANSISTOR	
				Q907	2SB1030RSTTA	TRANSISTOR	Δ
IC1	AN7351K	IC, PLAYBACK EQ. /MIC AMP		Q908	DTC114YSTP	TRANSISTOR	
IC2	M5218L	IC, PLAYBACK CORRECT PHASE		Q909	2SC3311AQSTA	TRANSISTOR	
IC201	HA13440MPCL	IC, MOTOR DRIVE		Q910	2SB1030RSTTA	TRANSISTOR	Δ
IC202	SN74LS04MEL	IC, INVERTER		Q911	2SC3311AQSTA	TRANSISTOR	
IC203	SN74LS74AMEL	IC, FLIP-FLOP		Q912	DTC114ESTP	TRANSISTOR	
IC301	UPC1297CA	IC, DOLBY BX PRO		Q913	2SC3311AQSTA	TRANSISTOR	
IC401, 402	TEA0665	IC, DOLBY B/C NR		Q914	DTC114ESTP	TRANSISTOR	
IC551	HD404302SA07	IC, MICROCOMPUTER; FL METER		Q915	DTC114YSTP	TRANSISTOR	
IC552	M5218L	IC, LEVEL METER AMP		Q916	2SB1030RSTTA	TRANSISTOR	
IC553	M5218L	IC, BUFFER AMP		Q917	2SD592A	TRANSISTOR	
IC701, 702	M5218L	IC, Class AA : H. P. AMP		Q918	2SC3311AQSTA	TRANSISTOR	
IC901	MB88511-224N	IC, MICROCOMPUTER; MECHANICAL		Q919-921	DTA114ESTP	TRANSISTOR	
IC902	BA6218	IC, REEL MOTOR CONTROL		Q923, 924	DTA114ESTP	TRANSISTOR	
IC903	M5218L	IC, MUSIC SELECTOR AMP		Q925	DTC114ESTP	TRANSISTOR	
IC971, 972	GP2SD06BC	IC, PHOTO COUPLER		Q926	2SB1030RSTTA	TRANSISTOR	
		TRANSISTOR(S)		Q927	2SC3311AQSTA	TRANSISTOR	(EB)
						DIODE(S)	
Q1, 2	2SJ164PQRTA	TRANSISTOR					
Q3-6	2SK381BCDTA	TRANSISTOR		D1, 2	MA167TA	DIODE	
Q7, 8	2SJ164PQRTA	TRANSISTOR		D3-8	MA165TA	DIODE	
Q9, 10	2SD1450RSTA	TRANSISTOR		D201	MA3056MTW	DIODE	
Q11-14	2SC3311AQSTA	TRANSISTOR		D301	MA165TA	DIODE	
Q17, 18	2SA1309AQSTA	TRANSISTOR		D302	MA4056MTA	DIODE	
Q201	2SD601RTW	TRANSISTOR		D303	MA165TA	DIODE	
Q301, 302	2SC3311AQSTA	TRANSISTOR		D551-554	MA165TA	DIODE	
Q303	2SB621ARSTA	TRANSISTOR	Δ	D555, 556	MA4051MTA	DIODE	
Q304	2SD592A	TRANSISTOR		D601-606	1SR35200TB	DIODE	Δ
Q305, 306	2SA1309AQSTA	TRANSISTOR		D607, 608	MA4091MTA	DIODE	
Q401-404	2SC3311AQSTA	TRANSISTOR		D609	MA4220M	DIODE	
Q551	2SA1309AQSTA	TRANSISTOR		D610	MA4062HTA	DIODE	
Q601	2SA1309AQSTA	TRANSISTOR	Δ	D611	1SR35200TB	DIODE	Δ
Q602, 603	2SC3311AQSTA	TRANSISTOR	Δ	D612	MA165TA	DIODE	
Q604	2SD2037EFTA	TRANSISTOR		D613	MA4120M	DIODE	
Q605	2SB1357EFTA	TRANSISTOR		D614	MA165TA	DIODE	
Q606	2SD2037EFTA	TRANSISTOR		D615	MA4330MTA	DIODE	
Q607	2SB621ARSTA	TRANSISTOR		D701	RFKFSB655EAK	L. E. D ASS'Y	
Q608	2SD2037EFTA	TRANSISTOR		D702	RFKFSB655EBK	L. E. D ASS'Y	
Q609	2SC3311AQSTA	TRANSISTOR	Δ	D901, 902	1SR35200TB	DIODE	
Q610	2SA1309AQSTA	TRANSISTOR	Δ	D903	MA165TA	DIODE	Δ
Q901	2SC3311AQSTA	TRANSISTOR		D904-909	MA165TA	DIODE	
Q902	DTA114ESTP	TRANSISTOR		D910	MA4051MTA	DIODE	
Q903	DTC114ESTP	TRANSISTOR		D911, 912	MA165TA	DIODE	
Q904	2SB1030RSTTA	TRANSISTOR	Δ	D913	MA4056H	DIODE	

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
D914	MA4091MTA	DIODE		S712	EVQQTG05R	SW, COUNTER MODE	
D915, 916	MA165TA	DIODE	△	S713	EVQQTG05R	SW, METER RANGE	
D917-921	MA165TA	DIODE		S714	EVQQTG05R	SW, MEMORY REPEAT	
D924	MA165TA	DIODE		S715	EVQQTG05R	SW, MEMORY STOP	
D971, 972	1SS133	DIODE		S716	EVQQTG05R	SW, APRS	
				S717	EVQQTG05R	SW, AUTO REC MUTE	
		VARIABLE RESISTOR(S)		S718	SSH1230	SW, POWER	
				S971	RSH1A89Z	SW, MODE	
VR1, 2	EVNDXAA00B53	V. R. PLAYBACK GAIN ADJ.		S972	RSH1A90Z	SW, HALF	
VR1A	EWGU2A029A54	V. R. REC. LEVEL CONTROL		S973	RSH1A90Z	SW, ATS	
VR2A	EVJ02SF06G15	V. R. BALANCE CONTROL		S975	RSH1A90Z	SW, REC INHIBIT	
VR3, 4	EVNDXAA00B14	V. R. OVERALL GAIN ADJ.		S976	RSH1A90Z	SW, ATS	
VR301, 302	EVNDXAA00B14	V. R. OVERALL FREQ. ADJ.					
VR303	EVJ02VF04B53	V. R. BIAS CURRENT ADJ.				CONNECTOR(S) AND SOCKET(S)	
VR701	EVU57A043A14	V. R. HEADPHONES CONTROL					
				CN1	SJT30545JQ	CONNECTOR(5P)	
		COIL(S)		CN3	SJSD1105	CONNECTOR(11P)	
				CN4	RJS1A1703	CONNECTORCONNECTOR(3P)	
L1, 2	RLZ0003	COIL		CN5	RJU003K010M	SOCKET(10P)	
L3, 4	SLQX272-1YT	COIL		CN6A-6C	RJS1A1703	CONNECTOR(3P)	
L301	SL09B4-K	COIL		CN7-9	RJU003K010M	SOCKET(10P)	
L302, 303	SL09B1-K	COIL		CN10	SJT30545JQ	CONNECTOR(5P)	
L401, 402	QLM9Z10K	COIL		CN11	SJT30345JQ	CONNECTOR(3P)	
L403, 404	SLM1B8-K	COIL		CN201	RJS1A1703	CONNECTOR(3P)	
				CN201A	RJS2T4ZA	CONNECTOR(2P)	
		TRANSFORMER(S)		CN601	RJS1A1101	SOCKET(1P)	△
				CN603	RJS1A1101	SOCKET(1P)	△
T601	RTP1K4B007-V	POWER TRANSFORMER	(EB) △	CN606-611	RJS1A1101	SOCKET(1P)	
T601	RTP1K4E008-V	POWER TRANSFORMER	(E, E5, EG) △	CP1	SJS50578JQ	SOCKET(5P)	
				CP2	SJTD513	CONNECTOR(5P)	
		OSCILLATOR(S)		CP5	RJT003K010	CONNECTOR(10P)	
				CP7-9	RJT003K010	CONNECTOR(10P)	
X551	EF0GC4004T4	CERAMIC FILTER		CP10	SJS50578JQ	SOCKET(5P)	
X901	EF0GC6004T4	CERAMIC FILTER		CP11	SJS50378JQ	SOCKET(3P)	
		DISPLAY TUBE				GND PART(S)	
FL551	RSL0017-F	DISPLAY TUBE (FL METER)		E1-3	SNE1004-1	GND PLATE	
				E701	SUSD165	GND SPRING	
		SWITCH(ES)					
						JACK(S)	
S701	EVQQTG05R	SW, STOP					
S702	EVQQTG05R	SW, F. F.		JK1	SJF3069N	TERMINAL BOARD	
S703	EVQQTG05R	SW, REW.		JK2	SJJ146B	JACK, HEADPHONES	
S704	EVQQTG05R	SW, PLAYBACK		JK3, 4	RJJ65MS01	JACK, MIC	
S705	EVQQTG05R	SW, RECORD		JK6	SJS9236	AC INLET	△
S706	EVQQTG05R	SW, PAUSE					
S707	EVQQTG05R	SW, DOLBY NR C				CERAMIC FILTER(S)	
S708	EVQQTG05R	SW, DOLBY NR B					
S709	EVQQTG05R	SW, MPX FILTER		CF201	RSXA3M74S01	CERAMIC FILTER	
S710	SSS166	SW, TIMER					
S711	EVQQTG05R	SW, COUNTER RESET				JAMPER(S)	
				J201-206	ERJ6GEY0R00V	CHIP JAMPER	


Notes : * Important safety notice:

Components identified by Δ mark have special characteristics important for safety. When replacing any of these components use only manufacturer's specified parts.

- * The parenthesized indications in the Remarks columns specify the areas. (Refer to the cover page for area.)
Parts without these indications can be used for all areas.

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		CABINET AND CHASSIS		40	RSC0076	SHIELD PLATE	
				41	RGLO030	PANEL LIGHT	
				42	RKU0009	BOTTOM BOARD	
1	RKM0036-K	CABINET		43	XTB3+10G	SCREW	
2	RYF0027	CASSETTE LID				PACKING MATERIAL	
3	RYQ0027	ORNAMENT					
4	SNE2129-1	SCREW		P1	RPG0255	CARTON BOX	
5	XTB3+8JFZ1	SCREW		P2	RPN0178	PAD, FRONT/BACK	
6	RMN0021	FL. HOLDER		P3	SPS5185	PAD, ACCESSORIES	
7	RSC0048	SHIELD PLATE		P4	SPP756	PROTECTION COVER	
8	RGR0024-A	REAR PANEL	(E)			ACCESSORIES	
8	RGR0024-C	REAR PANEL	(E5)				
8	RGR0024-E	REAR PANEL	(EB)				
8	RGR0024-L	REAR PANEL	(EG)	A1	RQF0239	INSTRUCTION MANUAL	(EG)
9	RGU0030	BUTTON, POWER		A1	RQF0240	INSTRUCTION MANUAL	(E, E5)
10	RGV0022	KNOB, TIMER		A1	RQF0241	INSTRUCTION MANUAL	(EB)
11	RGW0032	KNOB, BALANCE LEVEL		A2	SFDAC05E03	POWER CORD	(E, E5, EG) Δ
12	RGW0033	KNOB, REC LEVEL		A2	SJA193-1	POWER CORD	(EB) Δ
13	RKA0009-1	FOOT		A3	SJP2249-3	STEREO CONNECTION CABLE	
14	RFKNSB655EAK	FRONT GRILLE ASS'Y (1)					
14-1	RKW0038	TRANSPARENT PLATE					
15	RFKNSB655EBK	FRONT GRILLE ASS'Y (2)					
16	RMCO040	BRACKET					
17	RMCO056	SHIELD PLATE					
18	RMK0026-1	CHASSIS					
19	RMN0022	ORNAMENT					
20	RFKGSB655E-K	FRONT PANEL ASS'Y				MECHANISM UNIT	
21	RGK0117	ORNAMENT, BUTTON (A)					
22	RGK0118	ORNAMENT, BUTTON (B)		MECH1	RAA0802	MECHANISM ASS'Y	
23	RGU0130	BUTTON, EJECT					
24	RGU0131	BUTTON, COUNTER				PRINTED CIRCUIT BOARDS	
25	RGU0132	BUTTON, NOISE REDUCTION					
26	RGU0133	BUTTON, OPERATION		PWB1	REP0306A	MAIN P. C. B. ASS'Y	(E, E5, EG)
27	RKF0020A-3	CASSETTE HOLDER		PWB1	REP0306B	MAIN P. C. B. ASS'Y	(EB)
27-1	QBP2006A	SPRING, TAPE PRESSURE					
28	RME0032	SPRING		PWB2	REP0307A	SUB P. C. B. ASS'Y	
29	RME0034	SPRING					
30	RML0086	EJECT LEVER					
31	RMRO153	DAMPER GEAR ASS'Y					
32	XTB3+10JFZ	SCREW					
33	SUD444-1	WASHER					
34	SHE187-2	HOLDER					
35	SNE4021-1	NUT					
36	XTB3+16G	SCREW					
37	XTB3+20J	SCREW					
38	XTB3+8JFZ	SCREW					
39	XTB26+4FFZ	SCREW					


• Mechanical parts
(Top view)



Note:
When changing mechanism parts,
apply the specified grease to areas
marked "XX" as shown in the drawing.

Ref. No.	Part Name	Part No.
A	FLOIL AK-152	SZZOL 18
G	FLOIL 947P	RZZOL 02

(Bottom view)



REPLACEMENT PARTS LIST

Ref. No.	Part No.	Part Name & Description	Remarks	Ref. No.	Part No.	Part Name & Description	Remarks
		MECHANISM PARTS LIST		148	REP0268A	STATER P. C. B. ASS'Y	
101	QH1361A	SCREW					
102	SJH96-1	E HEAD					
103	RHE52012A	SCREW					
104	RJH4C35GZAM	R/P HEAD					
105	QBC1278A	SPRING					
106	RHM278ZA	SPACER					
107	RMD50132C	HEAD SPACER					
108	XTN2+5F	SCREW					
109	REX0075	LEAD WIRE BLOCK					
110	RXR0001	REEL TABLE					
111	RJW139ZA	SPRING					
112	RMA0047B	HEAD BASE					
113	RXQ0078	MAIN ROD ASS'Y					
114	RMD012-2	EJECT ROD(L)					
115	RME0018-1	SPRING					
116	RUB502Z	LEVER					
117	RME0020	SPRING					
118	RXL0007	BRAKE LEVER					
119	RJW142ZA	SPRING					
120	RXP0004	PINCH ROLLER ARM					
120-1	RJW140ZB	SPRING					
121	RFKRSB555E-K	CHASSIS ASS'Y					
122	XTN26+7J	SCREW					
123	MMN-6F4RA88	REEL MOTOR					
124	XTN26+26F	SCREW					
125	RMA0048A	FLYWHEEL PLATE					
126	XTN2+3F	SCREW					
127	XSN26+3	SCREW					
128	RMR0141	THRUST BEARING					
129	RXG0009	GEAR ASS'Y					
130	RDG0034	REEL MOTOR GEAR					
131	RUB428Z	MOVING IRON CORE					
132	RSJ0003	SOLENOID					
133	RXQ0011	BRAKE SOLENOID					
134	XTW2+8S	SCREW					
135	XTN26+4F	SCREW					
136	RDG0030	MAIN GEAR					
137	RXF0008	FLYWHEEL					
137-1	RNW139ZA	WASHER					
138	RML0037	LEVER					
139	RJW147ZA	SPRING					
140	RJS2T7ZA	CONNECTOR (2P)					
141	RMQ0037	FG YOKE					
142	RXG0003	REEL TABLE GEAR					
143	RJQ112ZA	SPRING					
144	RUS609Z	TAPE PRESSURE SPRING					
145	RJQ111ZA	SPRING					
146	RHE5204ZA	SCREW					
147	RJS11T7ZA	CONNECTOR (11P)					

RESISTORS & CAPACITORS

Notes : * Capacity value are in microfarads (uF) unless specified otherwise, P=Pico-farads (pF) F=Farads (F)
 * Resistance values are in ohms, unless specified otherwise, 1K=1,000(OHM) , 1M=1,000k(OHM)


Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks
		RESISTORS	R304, 305	ERDS2TJ100T	1/4W 10	R602	ERDS2TJ472T	1/4W 4.7K
			R306	ERDS2TJ471T	1/4W 470	R603	ERDS2TJ103T	1/4W 10K
			R307	ERDS2TJ222T	1/4W 2.2K	R604	ERDS2TJ472T	1/4W 4.7K △
R1, 2	ERDS2TJ223T	1/4W 22K	R308	ERDS2TJ472T	1/4W 4.7K	R605	ERDS1FVJ150T	1/2W 15 (E, E5, EG)
R3, 4	ERDS2TJ473T	1/4W 47K	R311, 312	ERDS2TJ100T	1/4W 10			△
R5, 6	ERDS2TJ102T	1/4W 1K	R313, 314	ERDS2TJ154T	1/4W 150K	R605	ERD2FCVG150T	1/4W 15 (EB) △
R7, 8	ERDS2TJ225T	1/4W 2.2M	R315, 316	ERDS2TJ153T	1/4W 15K	R606	ERDS1FVJ100T	1/2W 10 (E, E5, EG)
R9, 10	ERDS2TJ104T	1/4W 100K	R317	ERDS2TJ822T	1/4W 8.2K			△
R11, 12	ERDS2TJ183T	1/4W 18K	R318	ERDS2TJ272T	1/4W 2.7K	R606	ERD2FCVG100T	1/4W 10 (EB) △
R13, 14	ERDS2TJ101T	1/4W 100	R319	ERDS2TJ102T	1/4W 1K	R607, 608	ERDS2TJ102T	1/4W 1K
R15, 16	ERDS2TJ820T	1/4W 82	R320	ERDS2TJ332T	1/4W 3.3K	R611, 612	ERDS1FVJ270T	1/2W 27 (E, E5, EG)
R17, 18	ERDS2TJ153T	1/4W 15K	R321	ERDS1FVJ121T	1/2W 120 (E, E5, EG)			△
R19, 20	ERDS2TJ103T	1/4W 10K			△	R611, 612	ERD2FCVG270T	1/4W 27 (EB) △
R21, 22	ERDS2TJ564T	1/4W 560K	R321	ERDS1FVJ561T	1/2W 560 (EB) △	R613	ERDS2TJ222T	1/4W 2.2K △
R23, 24	ERDS2TJ682T	1/4W 6.8K	R322	ERDS2TJ563T	1/4W 56K	R614	ERDS2TJ222T	1/4W 2.2K
R25, 26	ERDS2TJ223T	1/4W 22K	R323	ERDS2TJ103T	1/4W 10K	R615	ERDS2TJ190T	1/4W 1.0 △
R27, 28	ERDS2TJ103T	1/4W 10K	R324	ERDS2TJ563T	1/4W 56K	R616	ERDS2TJ391T	1/4W 390 △
R29, 30	ERDS2TJ472T	1/4W 4.7K	R325-327	ERDS1FVJ561T	1/2W 560 (EB)	R617, 618	ERDS2TJ221T	1/4W 220 (EB)
R31, 32	ERDS2TJ392T	1/4W 3.9K	R401, 402	ERDS2TJ101T	1/4W 100	R617, 618	ERDS2TJ560T	1/4W 56 (E, E5, EG)
R33, 34	ERDS2TJ102T	1/4W 1K	R403, 404	ERDS2TJ272T	1/4W 2.7K	R619, 620	ERQ16NKR15E	1/5W 0.15 (EB) △
R35, 36	ERDS2TJ820T	1/4W 82	R405, 406	ERDS2TJ103T	1/4W 10K	R623, 624	ERDS2TJ101T	1/4W 100 (EB)
R39, 40	ERDS2TJ121T	1/4W 120	R407, 408	ERDS2TJ242	1/4W 2.4K	R625	ERDS2TJ181T	1/4W 180 (EB)
R41, 42	ERDS2TJ392T	1/4W 3.9K	R409-412	ERDS2TJ684T	1/4W 680K	R626, 627	ERDS2TJ101T	1/4W 100 (EB)
R43, 44	ERDS2TJ152T	1/4W 1.5K	R413, 414	ERDS2TJ562T	1/4W 5.6K	R628	ERDS2TJ103T	1/4W 10K
R45, 46	ERDS2TJ272T	1/4W 2.7K	R415, 416	ERDS2TJ102T	1/4W 1K	R629	ERDS2TJ472T	1/4W 4.7K △
R47, 48	ERDS2TJ104T	1/4W 100K	R417, 418	ERDS2TJ332T	1/4W 3.3K	R630	ERD2FCVG100T	1/4W 10 (EB) △
R49, 50	ERDS2TJ564T	1/4W 560K	R419, 420	ERDS2TJ333T	1/4W 33K	R631-636	ERDS2TJ221T	1/4W 220 (EB)
R51-56	ERDS2TJ223T	1/4W 22K	R421-424	ERDS2TJ823T	1/4W 82K	R637, 638	ERDS2TJ391T	1/4W 390 △
R57, 58	ERDS2TJ153T	1/4W 15K	R425, 426	ERDS2TJ683T	1/4W 68K	R701	ERDS2TJ821T	1/4W 820
R59, 60	ERDS2TJ182T	1/4W 1.8K	R427, 428	ERDS2TJ222T	1/4W 2.2K	R702	ERDS2TJ102T	1/4W 1K
R61, 62	ERDS2TJ333T	1/4W 33K	R429, 430	ERDS2TJ512	1/4W 5.1K	R703	ERDS2TJ122T	1/4W 1.2K
R63, 64	ERDS2TJ472T	1/4W 4.7K	R431, 432	ERDS2TJ242	1/4W 2.4K	R704	ERDS2TJ152T	1/4W 1.5K
R65, 66	ERDS2TJ102T	1/4W 1K	R551, 552	ERDS2TJ104T	1/4W 100K	R705	ERDS2TJ182T	1/4W 1.8K
R67, 68	ERDS2TJ223T	1/4W 22K	R553, 554	ERDS2TJ563T	1/4W 56K	R706	ERDS2TJ222T	1/4W 2.2K
R69, 70	ERDS2TJ472T	1/4W 4.7K	R555, 556	ERDS2TJ104T	1/4W 100K	R707	ERDS2TJ332T	1/4W 3.3K
R71, 72	ERDS2TJ561T	1/4W 560	R557, 558	ERDS2TJ220T	1/4W 22	R708	ERDS2TJ472T	1/4W 4.7K
R201	ERJ6GEYJ333V	1/10W 33K	R559, 560	ERDS2TJ152T	1/4W 1.5K	R709	ERDS2TJ682T	1/4W 6.8K
R202	ERJ6GEYJ683V	1/10W 68K	R561	ERDS2TJ102T	1/4W 1K	R710	ERDS2TJ123T	1/4W 12K
R203-205	ERJ6GEYJ1R5V	1/10W 1.5	R562	ERDS2TJ471T	1/4W 470	R711	ERDS2TJ223T	1/4W 22K
R206	ERJ6GEYJ222V	1/8W 2.2K	R563, 564	ERDS2TJ103T	1/4W 10K	R712	ERDS2TJ821T	1/4W 820
R207	ERJ6GEYJ182V	1/10W 1.8K	R565	ERDS2TJ105T	1/4W 1M	R713	ERDS2TJ102T	1/4W 1K
R208	ERJ6GEYJ222V	1/10W 2.2K	R569, 570	ERDS2TJ101T	1/4W 100	R714	ERDS2TJ122T	1/4W 1.2K
R209-211	ERJ6GEYJ4R7V	1/10W 4.7	R571	ERDS2TJ152T	1/4W 1.5K	R715	ERDS2TJ152T	1/4W 1.5K
R212, 213	ERJ6GEYJ152V	1/10W 1.5K	R572	ERDS2TJ102T	1/4W 1K	R716	ERDS2TJ182T	1/4W 1.8K
R214	ERJ6GEYJ822V	1/10W 8.2K	R573	ERDS2TJ560T	1/4W 56	R717	ERDS2TJ181T	1/4W 180
R215	ERJ6GEYJ101V	1/10W 100	R574	ERDS2TJ220T	1/4W 22	R718	ERDS2TJ331T	1/4W 330
R216	ERJ6GEYJ222V	1/8W 2.2K	R575	ERDS2TJ681T	1/4W 680	R719, 720	ERDS2TJ180	1/4W 18
R301	ERDS2TJ190T	1/4W 1.0	R576	ERDS2TJ681T	1/4W 680	R721, 722	ERDS2TJ330T	1/4W 33
R302, 303	ERDS2TJ183T	1/4W 18K	R601	ERDS2TJ472T	1/4W 4.7K △	R723, 724	ERDS2TJ100T	1/4W 10

Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks
R725, 726	ERDS2TJ102T	1/4W 1K	R958	ERDS2TJ103T	1/4W 10K	C39, 40	ECQB1H152JZ3	50V 1500P
R727, 728	ERDS2TJ332T	1/4W 3.3K	R959	ERDS2TJ152T	1/4W 1.5K	C41, 42	ECBT1H470J5	50V 47P
R901	ERDS2TJ105T	1/4W 1M	R960	ERDS2TJ472T	1/4W 4.7K	C43, 44	ECEA1CK100B	16V 10U
R902	ERDS2TJ103T	1/4W 10K	R961	ERDS2TJ821T	1/4W 820	C45, 46	ECEA1EK4R7B	25V 4.7U
R903	ERDS2TJ471T	1/4W 470	R962	ERDS2TJ183T	1/4W 18K	C47, 48	ECEA1HK010B	50V 1U
R904	ERDS2TJ103T	1/4W 10K	R963	ERDS2TJ473T	1/4W 47K	C49, 50	ECEA1CK100B	16V 10U
R905	ERDS2TJ182T	1/4W 1.8K	R964	ERDS2TJ392T	1/4W 3.9K	C51, 52	ECKT1H103ZF	50V 0.01U
R906	ERDS2TJ682T	1/4W 6.8K	R965	ERDS2TJ104T	1/4W 100K	C201	ECUV1E153MB	25V 0.015U
R907	ERDS2TJ103T	1/4W 10K	R970	ERDS2TJ222T	1/4W 2.2K	C202	ECUV1E104KB	25V 0.1U
R908	ERDS2TJ392T	1/4W 3.9K	R971	ERDS2TJ332T	1/4W 3.3K	C203, 204	ECEV1CA100R	16V 10U
R909	ERDS2TJ272T	1/4W 2.7K	R971A	ERDS2TJ271T	1/4W 270	C205, 206	ECUV1E104KB	25V 0.1U
R910	ERDS2TJ103T	1/4W 10K	R972	ERDS2TJ472T	1/4W 4.7K	C209-211	ECEV1EN4R7R	25V 4.7U
R911	ERDS2TJ392T	1/4W 3.9K	R972A	ERDS2TJ183T	1/4W 18K	C212-214	ECUV1H103ZFN	50V 0.01U
R912	ERDS2TJ272T	1/4W 2.7K	R973	ERDS2TJ682T	1/4W 6.8K	C215	ECUV1H472KB	50V 4700P
R913	ERDS2TJ561T	1/4W 560	R973A	ERDS2TJ271T	1/4W 270	C216	ECUV1E562KBN	25V 5600P
R914	ERDS2TJ102T	1/4W 1K	R974	ERDS2TJ123T	1/4W 12K	C217-219	ECUV1E104KB	25V 0.1U
R915	ERDS2TJ103T	1/4W 10K	R974A	ERDS2TJ183T	1/4W 18K	C301	ECQP1153JZ	100V 0.015U
R916	ERDS2TJ332T	1/4W 3.3K	R975	ERDS2TJ223T	1/4W 22K	C302	ECEA1EK4R7B	25V 4.7U
R917, 918	ERDS2TJ103T	1/4W 10K	R977	ERDS2TJ223T	1/4W 22K Δ	C303	ECKT1H392KB	50V 3900P
R919, 920	ERDS2TJ223T	1/4W 22K	R978	ERDS2TJ473T	1/4W 47K	C304, 305	ECKT1H222KB	50V 2200P
R922	ERDS2TJ472T	1/4W 4.7K	R979	ERDS2TJ272T	1/4W 2.7K	C306	ECKT1H682KB	50V 6800P
R923	ERDS2TJ152T	1/4W 1.5K	R980	ERDS2TJ472T	1/4W 4.7K	C310	ECKD1H472KB	50V 4700P
R924	ERDS2TJ223T	1/4W 22K Δ	R981	ERDS2TJ392T	1/4W 3.9K	C311	ECEA1AU101B	10V 100U
R925	ERDS2TJ821T	1/4W 820	R982	ERDS2TJ223T	1/4W 22K	C312	ECKT1H103ZF	50V 0.01U
R926	ERDS2TJ223T	1/4W 22K Δ	R983	ERDS2TJ103T	1/4W 10K	C313, 314	ECKT1H223ZF	50V 0.022U
R927	ERDS2TJ821T	1/4W 820	R984	ERDS2TJ472T	1/4W 4.7K (EB)	C315, 316	ECBT1H821KB5	50V 820P
R928	ERG1SJ150	1W 15 Δ	R985	ERDS2TJ222T	1/4W 2.2K (EB)	C317, 318	ECBT1H121KB5	50V 120P
R929	ERG1SJ180E	1W 18 Δ	R986	ERDS2TJ332T	1/4W 3.3K (EB)	C319, 320	ECQV1H563JZ3	50V 0.056U
R930	ERDS2TJ223T	1/4W 22K Δ	R987	ERDS2TJ822T	1/4W 8.2K	C321, 322	ECQB1H223JZ3	50V 0.022U
R931	ERDS2TJ821T	1/4W 820	R988	ERDS2TJ473T	1/4W 47K	C323, 324	ECQB1H103JZ3	50V 0.01U
R932	ERDS2TJ472T	1/4W 4.7K (EB)	R989	ERDS2TJ822T	1/4W 8.2K	C325, 326	ECKT1H122KB	50V 1200P
R932	ERDS2TJ103T	1/4W 10K (E, E5, EG)	R990	ERDS2TJ473T	1/4W 47K	C328	ECBT1H180J5	50V 18P
R933	ERDS2TJ472T	1/4W 4.7K				C329	ECEA1EK100B	25V 10U
R935	ERDS2TJ682T	1/4W 6.8K			CAPACITORS	C330	ECKT1H103ZF	50V 0.01U Δ
R936	ERDS2TJ223T	1/4W 22K				C331	ECBT1H180J5	50V 18P
R938	ERDS2TJ682T	1/4W 6.8K	C1, 2	ECEA1EK4R7B	25V 4.7U	C401, 402	ECBT1H820KB5	50V 82P
R939	ERDS2TJ223T	1/4W 22K	C3, 4	ECBT1H681KB5	50V 680P	C403, 404	ECEA1EK4R7B	25V 4.7U
R940, 941	ERDS2TJ562T	1/4W 5.6K	C5, 6	ECBT1H102KB5	50V 1000P	C405, 406	ECKT1H122KB	50V 1200P
R942	ERDS2TJ821T	1/4W 820	C7, 8	ECBT1H561KB5	50V 560P	C407, 408	ECKT1H152KB	50V 1500P
R943	ERDS2TJ223T	1/4W 22K	C9, 10	ECEA0JU101B	6.3V 100U	C409, 410	ECQB1H472JZ3	50V 4700P
R944, 945	ERDS1FVJ180T	1/2W 18 Δ	C11, 12	ECQB1H562JZ3	50V 5600P	C411, 412	ECEA1CK100B	16V 10U
R946	ERDS2TJ102T	1/4W 1K	C13, 14	ECEA1EK4R7B	25V 4.7U	C413, 414	ECQV1H473JZ3	50V 0.047U
R947, 948	ERDS2TJ103T	1/4W 10K	C15, 16	ECBT1H101KB5	50V 100P	C415, 416	ECQV1H224JZ3	50V 0.22U
R949	ERDS2TJ472T	1/4W 4.7K	C17, 18	ECQB1H822JZ3	50V 8200P	C417-420	ECEA1HCR68B	50V 0.68U
R950	ERDS2TJ821T	1/4W 820	C19, 20	ECEA1HCR47B	50V 0.47U	C421, 422	ECQV1H224JZ3	50V 0.22U
R951	ERDS2TJ101T	1/4W 100	C21, 22	ECEA1CK100B	16V 10U	C423, 424	ECQV1H473JZ3	50V 0.047U
R952	ERDS2TJ823T	1/4W 82K	C23, 24	ECQV1H273JZ	50V 0.027U	C425, 426	ECEA1CK100B	16V 10U
R953	ERDS2TJ393T	1/4W 39K	C27, 28	ECQB1H822JZ3	50V 8200P	C427, 428	ECQB1H472JZ3	50V 4700P
R954	ERDS2TJ472T	1/4W 4.7K	C29, 30	ECQV1H563JZ3	50V 0.056U	C429, 430	ECQB1H103JZ3	50V 0.01U
R955	ERDS2TJ102T	1/4W 1K	C33, 34	ECBT1H101KB5	50V 100P	C431, 432	ECKT1H102KB	50V 0.001U
R956	ERDS2TJ473T	1/4W 47K	C35, 36	ECEA1HK010B	50V 1U	C551, 552	ECQV1H104JZ3	50V 0.1U
R957	ERDS2TJ153T	1/4W 15K	C37, 38	ECQP1121JZ	100V 120P	C553, 554	ECEA0JKS101B	6.3V 100U

Ref. No.	Part No.	Values & Remarks	Ref. No.	Part No.	Values & Remarks			
C555	ECKT1H103ZF	50V 0.01U	C619, 620	ECKT1H103ZF	50V 0.01U Δ			
C556	ECEA1CK100B	16V 10U	C621	ECKT2H682PEL	500V 6800P Δ			
C557	ECEA1EK4R7B	25V 4.7U	C701	ECKT1H223ZF	50V 0.022U			
C558	ECEA1HK010B	50V 1U	C702, 703	ECKT1H103ZF	50V 0.01U			
C559-561	ECBT1C103NS5	16V 0.01U	C901	ECEA0JU222B	6.3V 2200U			
C563, 564	ECEA0JK101B	6.3V 100U	C902	ECKT1H103ZF	50V 0.01U			
C567	ECEA1VK100B	35V 10U	C903	ECEA1HK010B	50V 1U			
C568	ECEA1VK100B	35V 10U	C904	ECEA1EK4R7B	25V 4.7U			
C601	ECKT2H682PEL	500V 6800P	C905	ECKT1H103ZF	50V 0.01U			
C602, 603	ECEA1EU222E	25V 2200U Δ	C906	ECEA1CN100SB	16V 10U			
C604, 605	ECKT1H103ZF	50V 0.01U	C907	ECEA1HK010B	50V 1U			
C606, 607	ECEA1AU221B	10V 220U	C908	ECKT1H103ZF	50V 0.01U			
C608, 609	ECKT1H103ZF	50V 0.01U	C909	ECQB1H822JZ3	50V 8200P			
C610, 611	ECEA1AU102B	10V 1000U	C910	ECEA1CK100B	16V 10U			
C612	ECEA1EU222E	25V 2200U Δ	C911	ECBT1H470J5	50V 47P			
C613	ECKT1H103ZF	50V 0.01U	C912	ECEA1HK010B	50V 1U			
C615	ECEA1EK100B	25V 10U	C913	ECKT1H103ZF	50V 0.01U			
C617	ECEA1HU470B	50V 47U	C914	ECEA1EK4R7B	25V 4.7U			
C618	ECKT1H103ZF	50V 0.01U	C915	ECEA0JU101B	6.3V 100U			
C619, 620	ECKT1H103ZF	50V 0.01U Δ	C916	ECKT1H103ZF	50V 0.01U			
C621	ECKT2H682PEL	500V 6800P Δ	C917	ECEA1HK010B	50V 1U (EB)			
C701	ECKT1H223ZF	50V 0.022U	C918	ECKT1H103ZF	50V 0.01U			

PACKING

(Parts list on page 36.)



Service Manual

Cassette Deck
RS-B655

Supplement

Dolby NR-Equipped
Stereo Cassette Deck

Color

(K)... Black Type



*HX Pro headroom extension originated by Bang Olufsen and manufactured under license from Dolby Laboratories Licensing Corporation. "DOLBY", the double-D symbol, and "HX PRO" are trademarks of Dolby Laboratories Licensing Corporation.

Area

Country Code	Area	Color
(E, E5)	Continental Europe.	(K)
(EB)	Great Britain.	
(EG)	F.R. Germany & Italy.	

Please file and use this supplement manual together with the service manual for Model No. RS-B655, Order No. AD8907232C2.

Note:

- This supplement has been issued to correct an error in the "Replacement Parts List" on page 36.

DELETION

■ REPLACEMENT PARTS LIST (Page 36 of service manual.)

Note:

- Please remove the MECHANISM UNIT ASS'Y and the PRINTED CIRCUIT BOARD ASS'Y from the parts list because they are out of object in the replacement parts lists.

Ref. No.	Change of Part No.	Part Name & Description	Remarks
	ORIGINAL		
MECHANISM UNIT			
MECH1	RAA0802	MECHANISM ASS'Y	Deletion
PRINTED CIRCUIT BOARDS			
PWB1 (E, E5, EG)	REP0306A	MAIN P.C.B. ASS'Y	Deletion
PWB1 (EB)	REP0306B	MAIN P.C.B. ASS'Y	Deletion
PWB2	REP0307A	SUB P.C.B. ASS'Y	Deletion

Technics

Matsushita Electric Industrial Co., Ltd.
Central P.O. Box 288, Osaka 530-91, Japan

Printed in Japan
K890908250HK

Service Manual

Dolby NR-Equipped
Stereo Cassette Deck

Cassette Deck
RS-B665



* HX Pro headroom extension originated by Bang Olufsen and manufactured under license from Dolby Laboratories Licensing Corporation. "DOLBY", the double-D symbol, and "HX PRO" are trademarks of Dolby Laboratories Licensing Corporation.

RS-B555 MECHANISM SERIES (AR350)

Color

(K)... Black Type

Area

Country Code	Area	Color
(E)	Continental Europe.	(K)
(EB)	Great Britain.	
(EG)	F.R. Germany and Italy	

Please file and use this supplement manual together with the service manual for Model No. RS-B655, Order No. AD8907232C2.

CHANGE

CHANGE IN REPLACEMENT PARTS LIST

- Note:**
1. Mentioned in this parts list are only those different from Model No. RS-B655 (E, EB, EG) all other parts are the same as for RS-B655 (E, EB, EG).
 2. Important safety notice:
Components identified by Δ mark have special characteristics important for safety. When replacing any of these components use only manufacturer's specified parts.
 3. Parenthesized indications in "remarks" columns specify the area.
Parts without these indications can be used for all areas.

Ref. No.	Change of Part No.		Part Name & Description	Remarks
	RS-B655	➡ RS-B665		
RESISTORS				
R933	ERDS2TJ472T	ERDS2TJ332T	C. RESISTOR, 1/4W, 3.3KΩ	
R944, R945	ERDS1FVJ180T	ERDS1FVJ120T	C. RESISTOR, 1/2W, 12Ω	Δ
R959	ERDS2TJ152T	ERDS2TJ332T	C. RESISTOR, 1/4W, 3.3KΩ	
R985	ERDS2TJ222T	ERDS2TJ332T	C. RESISTOR, 1/4W, 3.3KΩ	(EB)
R986	ERDS2TJ332T	ERDS2TJ222T	C. RESISTOR, 1/4W, 2.2KΩ	(EB)
CAPACITORS				
C1, C2	ECEA1EK4R7B	ECA1HPXS4R7B	E. CAPACITOR, 50V, 4.7μF	
C9, C10	ECEA0JU101B	ECA0JPXS101B	E. CAPACITOR, 6.3V, 100μF	
C13, C14	ECEA1EK4R7B	ECA1HPXS4R7B	E. CAPACITOR, 50V, 4.7μF	
C19, C20	ECEA1HKR47B	ECA1HPXSR47B	E. CAPACITOR, 50V, 0.47μF	
C21, C22	ECEA1CK100B	ECA1CPXS100B	E. CAPACITOR, 16V, 10μF	
C35, C36	ECEA1HK010B	ECA1HPXS4R7B	E. CAPACITOR, 50V, 4.7μF	

Technics

Matsushita Electric Industrial Co., Ltd.
Central P.O. Box 288, Osaka 530-91, Japan

Ref. No.	Change of Parts No.		Part Name & Description	Remarks
	RS-B655	➡ RS-B665		
CAPACITORS				
C43, C44	ECEA1CK100B	ECA1CPXS100B	E. CAPACITOR, 16V, 10μF	
C45, C46	ECEA1EK4R7B	ECA1HPXS4R7B	E. CAPACITOR, 50V, 4.7μF	
C47, C48	ECEA1HK010B	ECA1HPXS010B	E. CAPACITOR, 50V, 1μF	
C49, C50	ECEA1CK100B	ECA1CPXS100B	E. CAPACITOR, 16V, 10μF	
C403, C404	ECEA1EK4R7B	ECA1HPXS4R7B	E. CAPACITOR, 50V, 4.7μF	
C411, C412	ECEA1CK100B	ECA1CPXS100B	E. CAPACITOR, 16V, 10μF	
C425, C426	ECEA1CK100B	ECA1CPXS100B	E. CAPACITOR, 16V, 10μF	
C602, C603	ECEA1EU222E	ECA1EPT222E	E. CAPACITOR, 25V, 2200μF	Δ
C610, C611	ECEA1AU102B	ECA1AAX102B	E. CAPACITOR, 10V, 1000μF	
TRANSISTORS				
Q303	2SB621ARSTA	2SB1357EFTA	TRANSISTOR	Δ
CONNECTORS				
D609	MA4220M	MA4220M	DIODE	(E, EG)
		MA4200M	DIODE	(EB)
CONNECTORS				
CN6A	RJS1A1073	RJS1A1704	CONNECTOR (4P)	
CN6B		RJS1A1705	CONNECTOR (5P)	
CN6C		—————	CONNECTOR (3P)	Deletion
JACKS				
JK2	SJJ146B	SJJD19	JACK, HEADPHONES	
JK3, JK4	RJJ65MS01	RJJ65MA01	JACK, MIC	
CABINET AND CHASSIS				
8	RGR0024—A	RGR0024—S	REAR PANEL	(E)
8	RGR0024—E	RGR0024—T	REAR PANEL	(EB)
8	RGR0024—L	RGR0024—U	REAR PANEL	(EG)
18	RMK0026—1	RMK0026—2	CHASSIS	
20	RFKGSB655E—K	RFKGSB665E—K	FRONT PANEL ASS'Y	
26	RGU0133	RGU133A	BUTTON, OPERATION	
42	RKU0009	RKU0009—1	BOTTOM BOARD	
43	XTB3+10G	XTB3+10GFZ	SCREW	
MECHANISM PARTS LIST				
109	REX0075	REX0075—2	LEAD WIRE BLOCK	
PACKING MATERIAL				
P1	RPG0255	RPG0524	CARTON BOX	
P2	RPN0178	—————	PAD, FRONT/BACK	Deletion
P3	SPS5185	SPSD152	PAD, ACCESSORIES	
P5	—————	RPN0366A	PAD (A)	Addition
P6	—————	RPN0366B	PAD (B)	Addition
P7	—————	RPN0366C	PAD (C)	Addition
P8	—————	RPN0366D	PAD (D)	Addition
ACCESSORIES				
A1	RQF0239	RFKSSB665E—K	INSTRUCTION MANUAL	(E)
A1	RQF0240	RQT0548—B	INSTRUCTION MANUAL	(EB)
A1	RQF0241	RQT0549—D	INSTRUCTION MANUAL	(EG)
A4	—————	RQA0013	WARRANTY CARD	Addition
A5	—————	RQCB0169	SERVICENTER LIST	Addition